

STA-RITE®

CRISTALFLO II

SAND FILTER

THE SOLUTION FOR CRYSTAL CLEAR WATER

You won't burn many calories maintaining the Sta-Rite® CristalFlo II sand filter. A small turn on the control valve puts the CristalFlo II filter to work cleaning itself. And this is one workout routine you won't have to do very often.

Through innovative engineering, the filter's dirt-handling capacity is maximised, which extends the time between cleanings (backwashing). But best of all, the CristalFlo II filter promises to make your pool water sparkle in the sun and shimmer in the moonlight.

Key Features

- ▶ Filter body manufactured of chemical-resistant, weather resistant, UV resistant, inalterable plastic.
- ▶ 6-Way Multi-port valve.
- ▶ Start/Clean pressure gauge dial for clear indication of backwash requirement.
- ▶ Pre-assembled collector in tank, ready to go.
- ▶ Perforated collector hub for high flow rates.
- ▶ Spigot-located collector to ensure balanced flow and efficient and reliable backwash.
- ▶ Easy to drain. No lost sand, thanks to a lateral and manual bleeder valve for water in the sand purge plug.
- ▶ 10 Year Pro-Rata Warranty*





6 Way Multiport Valve



'Collector On Hub' Design For High Flow



Start- Clean Pressure Gauge Dial

FILTER MODEL	FILTER AREA	MPV	SAND REQUIRED (KG)	ZEOLITE REQUIRED (KG)	GLASS REQUIRED (KG)		MAX FLOW	MIN BACKWASH
					COARSE	FINE		
CFSF-21-40	0.20m ²	21" / 40mm	80	75	35	45	180	120
CFSF-25-40	0.30m ²	25" / 40mm	120	105	45	75	280	180
CFSF-25-50	0.30m ²	25" / 50mm	120	105	45	75	300	180
CFSF-28-50	0.38m ²	25" / 50mm	150	120	60	90	340	230
CFSF-31-50	0.46m ²	31" / 50mm	200	165	75	125	400	260



1 - 21 Monash Drive,
Dandenong South,
VIC 3175
1300 137 344
www.pentairpool.com.au

Unless otherwise indicated, copyright in the content of this document is the property of Pentair Aquatic Systems Australia under Australian copyright law. Unless otherwise indicated, content may not be reproduced or transmitted without our prior written permission.