

TAGELUS

FIBREGLASS SAND FILTER

MAKING A TIME-PROVEN TECHNOLOGY BETTER

Sand filters have been installed on tens of thousands of pools for decades – a testament to their performance, value and ease of use. But not all sand filters are equal, because not all include design features that continuously flatten and level the sand inside the tank. This is the key to consistent performance and quicker cleaning cycles that keep pump operating costs low. It is also a key advantage when you select a Tagelus filter.





KEY FEATURES

- **Six Position Hi-Flow™ Valve** – Provides easy control of all filter functions and has a manual air relief valve and a sight glass to make inspection, maintenance and operation fast, easy and safer.
- **One-piece Tank** – One-piece fiberglass-reinforced tank with UV-resistant surface finish for years of service and exceptional strength.
- **Combination Drain** – Combination sand and water drain speeds servicing and winterizing.
- **Efficient Flow System Design** – Flow system design ensures maximum run times between backwashing to save you time and provide years of service with only periodic backwashing to remove trapped debris from the sand.
- **Special “Diffuser”** – Creates a uniform sand bed that consistently traps more dirt without impeding the water flow resulting in more effective filtration and longer run times between backwashing.
- **Threaded Internal Parts** – For fast and easy service.

*Terms & conditions apply.

MAXIMUM WATER CLARITY WITH MINIMAL ATTENTION

Tagelus filters remove particles large and small... so small that many are undetectable by the human eye, but in quantity make water cloudy. The reason thousands of Tagelus filters

have been installed by pool professionals worldwide is their consistency of performance over time. Plus, they go about their work without making work for you.



Six Position High-Flow Multi-Port Valve for easy mode selection



Built in sight glass and pressure gauge with adjustable cleaning indicators.



Built in air-bleed valve for safe and easy release of air at start-up.

MODEL	Product	MPV	Effective Filter Area (ft ² / m ²)	Min Flow Rate ¹ (LPM)	Max Flow Rate (LPM)	All Sand Required (kg)	Glass Required (kg)		Pool Size (based on 6hour turnover)
							Fine	Coarse	
140217	TA60D Tagelus Sand Filter 24"	1-1/2"/40mm	3.1 / 0.3	170	228	148	90	45	Up to 50,000L
145284	TA60D Tagelus Sand Filter 24" with 2" MPV	2"/50mm	3.1/0.3	170	250	148	90	45	Up to 80,000L
140218	TA100D Tagelus Sand Filter 30"	2"/50mm	4.9 / 0.5	280	379	273	150	90	Up to 120,000L



1-21 Monash Drive | Dandenong South, VIC 3175 | Australia | 1300 137 344 | pentairpool.com.au

Information contained here-in remains the property of Pentair under Australian copyright law. Content may not be reproduced or transmitted without our prior written permission.

Disclaimer: Pentair reserves the right to change product specifications and products details. Product images are for reference purposes only and may not represent the actual/current product.

©2023 Pentair. All rights reserved.